



# MPM Coolant Premium Longlife -40°C G12++ Ready to Use

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Issue date: 31-1-2020 Revision date: 22-6-2023 Supersedes: 16-8-2022 version: 4.1

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : MPM Coolant Premium Longlife -40°C G12++ Ready to Use  
UFI : 49HQ-GGA5-720C-1PHW  
Product code : 87000C  
Type of product : Anti-freezing agents  
Product group : Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Professional use  
Function or use category : Anti-freezing agents

##### 1.2.2. Uses advised against

No additional information available.

#### 1.3. Details of the supplier of the safety data sheet

MPM International Oil Company  
Cyclotronweg 1  
2629 HN Delft - Nederland  
T +31 (0)15 2514030  
[info@mpmoil.nl](mailto:info@mpmoil.nl) - [www.mpmoil.com](http://www.mpmoil.com)

#### 1.4. Emergency telephone number

Emergency number : +31 (0)15 2514030 (08.00 - 17.00 GMT+1)

Country	Official advisory body	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER	+44 20 7188 7188	

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4 H302  
Serious eye damage/eye irritation, Category 2 H319  
Specific target organ toxicity – Repeated exposure, Category 2 H373  
Full text of H- and EUH-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

No additional information available.

# MPM Coolant Premium Longlife -40°C G12++ Ready to Use

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS07

GHS08

CLP Signal word

: Warning

Contains

: 1,2 ethanediol

Hazard statements (CLP)

: H302 - Harmful if swallowed.

H319 - Causes serious eye irritation.

H373 - May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).

Precautionary statements (CLP)

: P264 - Wash hands thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P330 - Rinse mouth.

P102 - Keep out of reach of children.

### 2.3. Other hazards

Not determined.

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Water	CAS-No.: 7732-18-5 EC-No.: 231-791-2	$\leq 50$	Not classified
1,2 ethanediol	CAS-No.: 107-21-1 EC-No.: 203-473-3 EC Index-No.: 603-027-00-1 REACH-no: 01-2119456816-28	$\geq 45 - \leq 47,5$	Acute Tox. 4 (Oral), H302 STOT RE 2, H373
Potassium 2-ethylhexanoate	CAS-No.: 3164-85-0 EC-No.: 221-625-7 EC Index-No.: 221-625-7 REACH-no: 01-2119980714-29	$\geq 0,5 - < 1,5$	Skin Irrit. 2, H315 Eye Dam. 1, H318 Repr. 2, H361d

Comments

: Contains a small amount of Bitrex ( $> 25$  ppm), also known as Denatonium Benzoate. More information under section 11.

Full text of H- and EUH-statements: see section 16

# MPM Coolant Premium Longlife -40°C G12++ Ready to Use

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

General	: Remove the victim away from contaminated area. If unconscious, place in the recovery position and seek medical advice.
After inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
After skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention.
After eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophtalmologist if irritation persists.
After ingestion	: Do NOT induce vomiting. If the person is fully conscious, make him/her drink plenty of water. Never give an unconscious person anything to drink. Get immediate medical advice/attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

After inhalation	: Harmful if inhaled.
After skin contact	: May cause skin irritation / dermatitis.
After eye contact	: Causes eye irritation.
After ingestion	: Harmful if swallowed.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray, powder, foam and CO2. Fight larger fires with water spray or alcohol resistant foam.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: On exposure to high temperature, may decompose, releasing toxic vapours.
Hazardous decomposition products in case of fire	: Carbon monoxide (CO). Carbon dioxide (CO2). Nitrogen oxides (NOx).

#### 5.3. Advice for firefighters

Precautionary measures fire	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: Cool containers / tanks with spray water if possible. Use a water spray to cool exposed surfaces and to protect fire-fighters.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Ventilate well. Use protective clothing. Mark out the contaminated area with signs and prevent access to unauthorized personnel.
------------------	--

##### 6.1.1. For non-emergency personnel

Protective equipment	: Wear suitable protective clothing and eye/face protection.
----------------------	--

##### 6.1.2. For emergency responders

Protective equipment	: Wear suitable protective clothing and eye/face protection. Breathing apparatus.
----------------------	---

#### 6.2. Environmental precautions

Dilute with plenty of water. Avoid release to the environment.

# MPM Coolant Premium Longlife -40°C G12++ Ready to Use

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal.
- Other information : Provide adequate ventilation.

### 6.4. Reference to other sections

Information on safe handling - see Section 7. Information on personal protective equipment - see Chapter 8. Information on disposal - see Section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Provide local exhaust or general room ventilation. Avoid aerosol formation.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ensure adequate ventilation, especially in confined areas. Store in tightly closed, leak-proof containers. Keep in a cool, well-ventilated place away from heat.
- Storage conditions : Keep container tightly closed.
- Incompatible products : Strong bases. Oxidizing agent.
- Information on mixed storage : Keep in a cool, well-ventilated place away from acids.
- Storage area : Keep in a cool, well-ventilated place. Keep away from food, drink and animal feedingstuffs.
- Packaging materials : Keep only in the original container in a cool, well-ventilated place away from combustible materials.

### 7.3. Specific end use(s)

Anti-freezing agents.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1. National occupational exposure and biological limit values

1,2 ethanediol (107-21-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOELV TWA (mg/m <sup>3</sup> )	52 mg/m <sup>3</sup>
IOELV TWA (ppm)	20 ppm
EU - Binding Occupational Exposure Limit (BOEL)	
BOEL TWA	104 mg/m <sup>3</sup> TGG 15 min.
BOEL TWA [ppm]	40 ppm

#### 8.1.2. Recommended monitoring procedures

No additional information available.

#### 8.1.3. Air contaminants formed

No additional information available.

#### 8.1.4. DNEL and PNEC

No additional information available.

# MPM Coolant Premium Longlife -40°C G12++ Ready to Use

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 8.1.5. Control banding

No additional information available.

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Technical measures:

Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

#### Personal protective equipment:

Gloves. Protective goggles.

#### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

##### Eye protection:

No special eye protection equipment recommended under normal conditions of use. Eye protection should only be necessary where hot liquid could be splashed or sprayed

#### 8.2.2.2. Skin protection

##### Skin and body protection:

No special clothing/skin protection equipment is recommended under normal conditions of use

##### Hand protection:

protective gloves

#### 8.2.2.3. Respiratory protection

##### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

#### 8.2.2.4. Thermal hazards

No additional information available.

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

#### Other information:

Do not eat, drink or smoke when using this product. Avoid contact with skin.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Red.
Appearance	: Hygroscopic.
Odour	: Slight.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: -18 °C
Boiling point	: > 107 °C ASTM D 1120
Flammability	: Not available
Explosive properties	: Product is not explosive.
Oxidising properties	: No oxidising properties.
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available

# MPM Coolant Premium Longlife -40°C G12++ Ready to Use

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Flash point	: 111 °C @ (CAS: 107-21-1, ethaandiol; ethyleenglycol)
Auto-ignition temperature	: Not determined.
Decomposition temperature	: Not determined.
pH	: 8,4 (7,5 – 9) ASTM D 1287
Viscosity, kinematic	: Not determined.
Solubility	: In water, material soluble.
Log Kow	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: ≈ 1063 (1055 – 1070) kg/m <sup>3</sup> @ 20°C
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle size	: Not determined.
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available.

#### 9.2.2. Other safety characteristics

Miscibility : water,acetone,alcohol

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No information available.

### 10.2. Chemical stability

No additional information available.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Contact with incompatible materials.

### 10.5. Incompatible materials

No information available.

### 10.6. Hazardous decomposition products

None under normal conditions.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met.)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met.)

# MPM Coolant Premium Longlife -40°C G12++ Ready to Use

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

1,2 ethanediol (107-21-1)	
LD50 dermal	> 3500 mg/kg (Mouse)
LC50 Inhalation - Rat	> 2,5 mg/l 6h
Potassium 2-ethylhexanoate (3164-85-0)	
LD50 oral rat	2043 mg/kg OECD 401
LD50 dermal rat	> 2000 mg/kg OECD 402
ATE CLP (oral)	2043 mg/kg bodyweight
Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met.) pH: 8,4 (7,5 – 9) ASTM D 1287
Serious eye damage/irritation	: Causes serious eye irritation. pH: 8,4 (7,5 – 9) ASTM D 1287
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met.)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met.)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met.)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met.)
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met.)
STOT-repeated exposure	: May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).
1,2 ethanediol (107-21-1)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Potassium 2-ethylhexanoate (3164-85-0)	
NOAEL (oral, rat, 90 days)	≈ 300 mg/kg bodyweight OECD 408
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met.)
MPM Coolant Premium Longlife -40°C G12++ Ready to Use	
Viscosity, kinematic	Not determined.

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

### 11.2.2. Other information

Other information : The mixture contains a small amount of Bitrex, which is a bittering agent and is a general description of chemical additives that are added to dangerous products to give it a bitter taste, which creates a strong aversion and as such prevents accidental poisonings for young people in particular children and pets. There are a number of possible chemicals that can be used, but the best known is the Denatonium benzoate (CAS 3734-33-6).

## SECTION 12: Ecological information

### 12.1. Toxicity

General : According to the criteria of the EC-classification and labelling "dangerous for the environment" (93/21/EEC) the material/product is not to be classified as dangerous to the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

# MPM Coolant Premium Longlife -40°C G12++ Ready to Use

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

1,2 ethanediol (107-21-1)	
LC50 fish 1	72860 mg/l @96h Dikkop witvis ( Pimephales promelas )
EC50 Daphnia 1	> 100 mg/l OECD 202 (Daphnia magna)
EC50 96h - Algae [1]	6500 – 13000 mg/l (EPA 600/9-78-018)
NOEC (chronic)	≥ 1000 mg/l Mysidopsis bahia (Duration: 23 d)
NOEC chronic fish	15380 mg/l (EPA EPA 600/4-89/001 (7d), Pimephales promelas) semi-static
NOEC chronic crustacea	8590 mg/l (EPA 600/4-89/001, Ceriodaphnia dubia)

Potassium 2-ethylhexanoate (3164-85-0)	
LC50 fish 1	> 100 mg/l OECD 203 Oryzias latipes
EC50 Daphnia 1	910 mg/l OECD 202 Daphnia magna
EC50 Daphnia 2	112,1 mg/l static (bacteria) (DIN 38412, part 8, Pseudomonas putida
EC50 72h - Algae [1]	49,3 mg/l static read across CAS 149057-5 nominal
NOEC (chronic)	25 mg/l Daphnia magna @21d
NOEC chronic crustacea	25 mg/l Daphnia @OECD 211, Daphnia magna 21d

### 12.2. Persistence and degradability

1,2 ethanediol (107-21-1)	
Persistence and degradability	Readily biodegradable.

Potassium 2-ethylhexanoate (3164-85-0)	
Biodegradation	99 % OECD 301E

### 12.3. Bioaccumulative potential

MPM Coolant Premium Longlife -40°C G12++ Ready to Use	
Bioaccumulative potential	No relevant information available.

1,2 ethanediol (107-21-1)	
Log Pow	-1,36

Potassium 2-ethylhexanoate (3164-85-0)	
Log Pow	2,96 OECD Guideline 107

### 12.4. Mobility in soil

MPM Coolant Premium Longlife -40°C G12++ Ready to Use	
Soil	No additional information available.

### 12.5. Results of PBT and vPvB assessment

MPM Coolant Premium Longlife -40°C G12++ Ready to Use	
Not determined.	

### 12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : The product does not contain any substances with endocrine disrupting properties.



# MPM Coolant Premium Longlife -40°C G12++ Ready to Use

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 12.7. Other adverse effects

Other adverse effects : No additional information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste) : Comply with local regulations for disposal.  
Additional information : This material and its container must be disposed of in a safe way, and as per local legislation.  
European List of Waste (LoW) code : 16 01 14\* - antifreeze fluids containing dangerous substances

## SECTION 14: Transport information

In accordance with ADR / IMDG

### 14.1. UN number or ID number

UN-No. : Not regulated  
UN-No. (IMDG) : Not regulated

### 14.2. UN proper shipping name

Proper Shipping Name (ADR) : Not regulated  
Proper Shipping Name (IMDG) : Not regulated

### 14.3. Transport hazard class(es)

#### ADR

Transport hazard class(es) (ADR) : Not regulated

#### IMDG

Transport hazard class(es) (IMDG) : Not regulated

### 14.4. Packing group

Packing group (ADR) : Not regulated  
Packing group (IMDG) : Not regulated

### 14.5. Environmental hazards

Dangerous for the environment : No  
Marine pollutant : No  
Other information : No supplementary information available

### 14.6. Special precautions for user

#### Overland transport

Not regulated

#### Transport by sea

Not regulated

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

# MPM Coolant Premium Longlife -40°C G12++ Ready to Use

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Contains no substance(s) listed on the REACH Candidate List

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

### 15.1.2. National regulations

No additional information available.

### 15.2. Chemical safety assessment

No additional information available.

## SECTION 16: Other information

### Full text of H- and EUH-statements

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H361d	Suspected of damaging the unborn child
H373	May cause damage to organs through prolonged or repeated exposure.
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2

### SDS MPM REACH

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.