



## 02000A Motor Oil 20W-50 Turbo Universal

Document version: May 18, 2024



### Description

This universal multigrade mineral motor oil is suitable for naturally aspirated or turbocharged diesel engines. This oil is also suitable for most normal duty petrol engines and is extremely suitable for use in warm climates.

### According to the specifications of

ACEA A3/B4 / E3  
API CG-4 / SJ  
Allison C4  
MAN M 3275  
MB 228.3 / 229.1  
MTU Type 2  
Mack EO-L  
Volvo VDS-2

### Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
02001A	1 L	6	450
02004A	4 L	4	112
02005A	5 L	4	112
02020A	20 L	1	30
02060A	60 L	1	6
02205A	205 L	1	2
02999A	1000 L	1	-
P02000A	1 L	1	-

## Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.896	kg/l	
Viscosity	20W-50		
Kinematic Viscosity at 40°C	170	mm <sup>2</sup> /s	
Kinematic Viscosity at 100°C	19.2	mm <sup>2</sup> /s	
Viscosity Index	129		
Dynamic Viscosity at -15°C	8200	mPa.s	
Flashpoint COC	235	°C	
Pourpoint	-24	°C	
Total Base Number	8.7	mgKOH/g	
Sulphated Ash	1.33	mass%	

These characteristics are typical of current production. Variations in these characteristics may occur.