



# 54000 4-Stroke Motorcycle Oil 10W-40 Semi Synthetic

Document version: May 18, 2024



## Description

MPM 4-Stroke Motorcycle Oil 10W-40 Semi Synthetic Ester Technology is suitable for air- and water-cooled 4-stroke engines and gearboxes. This engine oil gives high performance protection to engines and gearboxes under heavy conditions due to the high-quality base oils with ester blend. The combination of exceptional anti-wear/friction additives and the lubricity of the mixture reduces oil consumption and extends engine life. This multi-grade SAE 10W-40 engine oil has been developed for motorcycles with or without wet clutches and is backwards compatible with API SG, SH, SJ, SL, and SM specifications.

## According to the specifications of

API SN  
JASO MA / MA2

## Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
54001	1 L	6	450
54004	4 L	4	112
54020	20 L	1	30
54060	60 L	1	6
54205	205 L	1	2
54999	1000 L	1	-

## Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.854	kg/l	ASTM D4052
Colour	Red		VISUAL
Viscosity	10W-40		
Kinematic Viscosity at 40°C	95	mm <sup>2</sup> /s	ASTM D445
Kinematic Viscosity at 100°C	14.9	mm <sup>2</sup> /s	ASTM D445
Viscosity Index	165		ASTM D2270
Pourpoint	-45	°C	ASTM D6892
Total Base Number	7.3	mgKOH/g	ASTM D2896

These characteristics are typical of current production. Variations in these characteristics may occur.