



05000ST Motor Oil 5W-30 Premium Synthetic ST

Dokumentversjon: 14. apr. 2024



Beskrivelse

This Premium Synthetic 'Mid SAPS ' engine oil is designed for gasoline and diesel engines equipped with an exhaust after-treatment system. This special formulation complies to the Stellantis FWP9.55535/03 specification which is mandatory for DV5R engines until OPR 16885. These D5VR engines are used in Citroën, DS, Peugeot, Fiat, Toyota, Opel and Vauxhall. The optimized cleanliness, reduces wear increases the lifetime of the mechanical components and the engine. This engine oil is also suitable for engines requiring PSA B71 2290 specification with viscosity grade 5W-30.

Søknad manual

Ifølge spesifikasjonene til

ACEA C3
API SN Plus
PSA B71 2290
Stellantis FPW9.55535/03

Emballasje enheter

ART. NR.	VOLUM	ANTALL PER ENHET	ANTALL PER PALL
05001ST	1 L	6	450
05005ST	5 L	4	112
05020ST	20 L	1	30
05060ST	60 L	1	6
05205ST	205 L	1	2
P05000ST	1 L	1	-

Standard analyser

TEST	VERDI		METHOD
Density Ved 15°C	0.847	kg/l	ASTM D4052
Kinematic Viscosity Ved 40°C	66.3	mm ² /s	ASTM D445
Kinematic Viscosity Ved 100°C	11.3	mm ² /s	ASTM D445
Viscosity Index	170		ASTM 2270
Flashpoint COC	254	°C	ASTM D92
Pourpoint	-42	°C	ASTM D97

Disse egenskapene er typiske for nåværende produksjon. Variasjoner i disse egenskapene kan forekomme.