



08000AT Motor Oil 0W-16 Premium Synthetic Advanced Technology

Dokumentversjon: 14. apr. 2024



Beskrivelse

This MPM premium synthetic engine oil is based on a modern advanced technology which makes it possible to achieve the most effective fuel saving. Using high-quality base oils in combination with specially selected additives, this motor oil with very low viscosity provides excellent engine wear protection.

The unique fuel-saving effect also achieves a reduction in CO₂ emissions and fits perfectly with the philosophy of hybrid vehicles. This high-quality engine oil is suitable for all vehicles where one SAE 0W-16 is prescribed.

Ifølge spesifikasjonene til

API SN Plus / SN Plus-RC / SP / SP-RC
ILSAC GF-6B

Emballasje enheter

ART. NR.	VOLUM	ANTALL PER ENHET	ANTALL PER PALL
08001AT	1 L	6	450
08005AT	5 L	4	112
08020AT	20 L	1	30
08060AT	60 L	1	6
08205AT	205 L	1	2
08999AT	1000 L	1	-
P08000AT	1 L	1	-

Standard analyser

TEST	VERDI		METHOD
Density Ved 15°C	0.847	kg/l	ASTM D4052
SAE	0W-16		
Kinematic Viscosity Ved 40°C	34.6	mm ² /s	ASTM D445
Kinematic Viscosity Ved 100°C	6.8	mm ² /s	ASTM D445
Viscosity Index	160		ASTM D2270
Flashpoint COC	220	°C	ASTM D92
Pourpoint	-45	°C	ASTM D7346
Total Base Number	7.3	mgKOH/g	ASTM D2896
Sulphated Ash	0.85	mass%	ASTM D874

Disse egenskaperne er typiske for nåværende produksjon. Variasjoner i disse egenskaperne kan forekomme.