



## 86000ALP Antifreeze Low Phosphate Concentrate

Dokumentversjon: 14. apr. 2024



### Beskrivelse

This Long life silicate-free antifreeze is based on Phosphated Organic Additive Technology (P-OAT) and is especially suitable for use in Japanese and Korean vehicles. This high quality antifreeze is extremely suitable in engines manufactured from aluminium, cast iron or combinations of the two metals and in cooling systems made of aluminium or copper alloys.

MPM 86000ALP antifreeze should be diluted with at least 30% demineralized water before use and does not contain nitrites, borates nor amines.

### Ifølge spesifikasjonene til

ASTM D3306 / D6210  
Honda Type 2  
JIS K 2234-2006 Class II  
Mazda FL22  
Mitsubishi Dia Queen Super Long life Coolant  
Nissan L255N  
Subaru 16218  
Suzuki (Super) Long Life Coolant  
Toyota TSK 2601G-8A

### Emballasje enheter

ART. NR.	VOLUM	ANTALL PER ENHET	ANTALL PER PALL
86001ALP	1 L	6	450
86005ALP	5 L	4	112
86020ALP	20 L	1	30
86060ALP	60 L	1	6
86205ALP	205 L	1	2
86999ALP	1000 L	1	-

## Standard analyser

TEST	VERDI		METHOD
Density Ved 15°C	1.119	kg/l	ASTM D1122
Colour	dark blue		
Freezing Point 50% fortynnet	-37	°C	ASTM D1177
pH	8,4		ASTM D1287
Boiling Point	178	°C	ASTM D1120

Disse egenskapene er typiske for nåværende produksjon. Variasjoner i disse egenskapene kan forekomme.