



BL020000 Marine FC-W Engine Oil 4-Stroke Outboard EHP 10W-30

Dokumentversjon: 14. apr. 2024



Beskrivelse

This marine FC-W outboard oil is a four-stroke engine oil based on high quality base oils with special additives. Because of his excellent 'shear stability' in combination with a very strong anti-corrosion, oxidation and wear properties this four-stroke oil is suitable for use in high speed and heavy duty outboard engines as e.g. Mercury engines. This outboard engine oil meets the latest requirements set by the NMMA. The specific marine engine oil is not suitable for use in outboard engines with after treatment system and for us in cars.

Ifølge spesifikasjonene til

API SJ / SL
NMMA FC-W

Emballasje enheter

ART. NR.	VOLUM	ANTALL PER ENHET	ANTALL PER PALL
BL020001	1 L	6	450
BL020005	5 L	4	112
BL020020	20 L	1	30
BL020060	60 L	1	6
BL020205	205 L	1	2
BL020999	1000 L	1	-
PBL020000	1 L	1	-

Standard analyser

TEST	VERDI		METHOD
Density Ved 15°C	0.871	kg/l	
Viscosity SAE	10W-30 10		
Kinematic Viscosity Ved 40°C	76.6	mm ² /s	
Kinematic Viscosity Ved 100°C	11.8	mm ² /s	
Viscosity Index	149		
Dynamic Viscosity Ved -25°C	5000	mPa.s	
Flashpoint COC	216	°C	
Pourpoint	-27	°C	
Total Base Number	7.7	mgKOH/g	

Disse egenskaperne er typiske for nåværende produksjon. Variasjoner i disse egenskaperne kan forekomme.