



41000C Motor Oil SAE 30 Single Grade Classic

Document version: May 18, 2024



Description

This mineral SAE 30 Super Single Grade oil has been developed for a wide range of purposes and is extremely suitable for stationary engines, for industrial transmissions and for hydraulic systems.

According to the specifications of

API CC / SF
CCMC D1
CCMC G2

Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 41001C | 1 L | 6 | 450 |
| 41005C | 5 L | 4 | 112 |
| 41020C | 20 L | 1 | 30 |
| 41060C | 60 L | 1 | 6 |
| 41205C | 205 L | 1 | 2 |
| 41999C | 1000 L | 1 | - |
| P41000C | 1 L | 1 | - |

Standard analyses

| TEST | VALUE | METHOD |
|------------------------------|--------|--------------------|
| Density at 15°C | 0.891 | kg/l |
| Viscosity | SAE 30 | |
| Kinematic Viscosity at 40°C | 103 | mm ² /s |
| Kinematic Viscosity at 100°C | 11.3 | mm ² /s |
| Viscosity Index | 95 | |
| Flashpoint COC | 240 | °C |
| Pourpoint | -21 | °C |
| Total Base Number | 4.4 | mgKOH/g |
| Sulphated Ash | 0.76 | mass% |

These characteristics are typical of current production. Variations in these characteristics may occur.