



## BL001000BIO Marine TC-W3 Oil 2-Stroke High Performance Biodegradable

Document version: 18 May 2024



### Description

This marine TC-W3 Oil 2-stroke biolube is a full synthetic biodegradable 2-stroke oil for use in water-cooled outboard engines of watercrafts, jet skis and Evinrude E-TEC engines. This thermally stable oil ensures outstanding piston cleanliness and protection against rust.

The biodegradable 2-stroke oil is readily miscible with gasoline and suitable as self-mixing or in oil injection systems.

The mixing ratio of the oil is 2% (1:50) and 1% (1:100) in accordance with the recommendation with the engine manufacturer.

### Specifications

API TC+  
CEC L-33-T-82 > 80%  
NMMA TC-W3

### Packaging units

| ART. NR.    | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|-------------|--------|----------------|------------------|
| BL001001BIO | 1 L    | 6              | 450              |
| BL001005BIO | 5 L    | 4              | 112              |
| BL001020BIO | 20 L   | 1              | 30               |
| BL001060BIO | 60 L   | 1              | 6                |
| BL001205BIO | 205 L  | 1              | 2                |
| BL001999BIO | 1000 L | 1              | -                |

## Standard analyses

| TEST                         | VALUE |                    | METHOD |
|------------------------------|-------|--------------------|--------|
| Density at 15°C              | 0.897 | kg/l               |        |
| Colour                       | green |                    |        |
| Kinematic Viscosity at 40°C  | 47    | mm <sup>2</sup> /s |        |
| Kinematic Viscosity at 100°C | 8.5   | mm <sup>2</sup> /s |        |
| Viscosity Index              | 170   |                    |        |
| Flashpoint COC               | 105   | °C                 |        |
| Pourpoint                    | -36   | °C                 |        |
| Total Base Number            | 9.6   | mgKOH/g            |        |

These characteristics are typical of current production. Variations in these characteristics may occur.